



### Main

Commercial Status	Commercialised
Aesthetic name	Unica Top - Unica Class
Product or component type	Switch
Device presentation	Mechanism
Switch function	2-way
Provided equipment	Internal power connection
Rated current	10 AX, 250 V AC, 50/60 Hz
Actuator	Rocker
Number of modules	1 module
Fixing mode	Clip-in
Cover plate colour tint	Graphite

### Complementary

Contacts type and composition	1 C/O
Opening distance	> 3 mm
Connections - terminals	Screwless terminals
Cable cross section	<= 2.5 mm <sup>2</sup> (rigid) <= 2.5 mm <sup>2</sup> (flexible)
Minimum load breaking capacity	200 operations 1.25 I <sub>n</sub> and 1.1 I <sub>un</sub> , cos phi: 0.3
Electrical durability	10000 cycles
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	> 2000 V
Material	Mechanism cover: ABS (acrylonitrile butadiene-styrene)
Standards	EMC directive EN 60669-1 LV directive
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Embedding depth	22 mm
Depth	34 mm
Width	22.5 mm
Height	45 mm
Product weight	0.019 kg

### Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0622 - <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Period	18 months
--------	-----------