



Main

Commercial Status	Commercialised
Aesthetic name	Unica Top - Unica Class
Product or component type	Switch
Device presentation	Mechanism
Switch function	Intermediate
Provided equipment	Internal power connection
Rated current	10 AX, 250 V AC, 50/60 Hz
Actuator	Rocker
Number of modules	1 module
Fixing mode	Clip-in
Cover plate colour tint	Graphite

Complementary

Contacts type and composition	2 C/O
Opening distance	> 3 mm
Connections - terminals	Screwless terminals
Cable cross section	<= 2.5 mm ² (rigid) <= 2.5 mm ² (flexible)
Minimum load breaking capacity	200 operations 1.25 I _n and 1.1 I _{un} , cos phi: 0.3
Electrical durability	10000 cycles
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	> 2000 V
Material	Mechanism cover: ABS (acrylonitrile butadiene-styrene)
Standards	EMC directive EN 60669-1 LV directive
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Embedding depth	22 mm
Depth	34 mm
Width	22.5 mm
Height	45 mm
Product weight	0.0231 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0622 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Period	18 months
--------	-----------