



## Main

Commercial Status	Commercialised
Aesthetic name	Unica Top - Unica Class
Product or component type	Movement detector
Device presentation	Mechanism
[Ue] rated operational voltage	230 V AC (+/- 10 %), 50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Cover plate colour tint	Graphite
Mounting height	> 1.2...< 2.15 m

## Complementary

Power range	2300 W
Load type	Compact fluorescent lamp - 500 VA Fluorescent tube (diameter: 26...38 mm): 1 1-10 V dimmable electronic ballast - 2000 VA, cos phi: 0.9 230 V AC contactor - 200 VA 230 V AC convector - 2300 W 230 V AC fan - 200 VA Low voltage lamps with electronic transformer - 1150 VA Low voltage halogen lamp with wire-wound transformer - 1500 VA 230 V AC halogen lamp - 2000 W 230 V AC incandescent lamp - 2300 W
Movement detection area	10 x 20 m (PIR mounting height 2.15 m) 9 x 18 m (PIR mounting height 1.2 m)
Presence detection area	5 x 10 m (PIR mounting height 1.2 m) 6 x 12 m (PIR mounting height 2.15 m)
Detection angle	Full 180° Partial 90° left or right
Selection modes	A: automatic M: manual S: slave
Type of setting	Adjustable disconnection time and brightness
Control type	Manual override with 5 pushbuttons maximum
Wiring configuration	3 wires with neutral
Light intensity adjustment	5...1000 lux
Time delay	2 s...20 min
Marking	L+N
Connections - terminals	Screw terminals
Number of cables	2 rigid: <= 2.5 mm <sup>2</sup> 2 flexible: <= 2.5 mm <sup>2</sup>
Material	Mechanism cover: ASA + PC
Standards	EN 60669-2-1
Product certifications	Aenor CE
Ambient air temperature for operation	-5...35 °C
Ambient air temperature for storage	-20...55 °C
Relative humidity	0..5 %
Embedding depth	34 mm
Depth	58 mm
Width	45 mm

Height	45 mm
Product weight	0.076 kg

## Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

## Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0644 - <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference contains SVHC above the threshold - <a href="#">go to CaP for more details</a>
Product environmental profile	Available

## Contractual warranty

Period	18 months
--------	-----------