



Main

Commercial Status	Commercialised
Aesthetic name	Unica (standard aesthetic)
Product or component type	Weekly-programmable thermostat
Device presentation	Mechanism
[Ue] rated operational voltage	230 V AC (+/- 10 %), 50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Cover plate colour tint	Ivory
Mounting height	> 1.5 m

Complementary

Programmable temperature	Differential Frost protection Tmax Tmin
Temperature setting range	5...35 °C
Measurement accuracy	0.5 °C
Contacts type and composition	1 C/O
Load interrupting current	Resistive: 8 A Inductive: 5 A
Information displayed	Air-conditioning on Ambient room temperature 0 to 45 °C Day Time
Backup time	7 days time and program saving
Marking	L+N
Connections - terminals	Screw terminals
Number of cables	2 rigid: <= 2.5 mm ² 2 flexible: <= 2.5 mm ²
Material	Mechanism cover: ASA + PC
Standards	EN 60730-2-9
Product certifications	Aenor CE
Electronic switch type	Type 1B
Software class	Class A
Electrical insulation class	Class II
Ambient air temperature for operation	0...50 °C
Ambient air temperature for storage	-5...55 °C
Relative humidity	20...85 %
Embedding depth	33 mm
Depth	45 mm
Width	45 mm
Height	45 mm
Product weight	0.0625 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0805 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available

Contractual warranty

Period	18 months
--------	-----------