



## Main

Commercial Status	Commercialised
Aesthetic name	Unica (standard aesthetic)
Product or component type	Time delay switch
Device presentation	Mechanism
[Ue] rated operational voltage	230 V AC (+/- 10 %), 50 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Cover plate colour tint	White

## Complementary

Contacts type and composition	1 NO
Load type	Contactor - 200 W LED lamp Compact fluorescent lamp - 1840 W Fluorescent tube conventional ballast - 1840 VA Low voltage halogen lamp with electronic transformer - 1840 VA Low voltage halogen lamp with ferromagnetic transformer - 1840 VA 230 V AC convector - 1840 W 230 V AC fan - 600 W 230 V AC halogen lamp - 1840 W 230 V AC incandescent lamp - 1840 W
Load interrupting current	8 A
Protection type	Current protection Electronic overvoltage protection
Time delay	2 s...12 min
Pilot light	Blue neon locator lamp: 1 mA (temperature : max +15 °C above ambient temperature)
Marking	L+N
Connections - terminals	Screw terminals
Number of cables	1 rigid: <= 1.5 mm <sup>2</sup> 2 flexible: <= 2.5 mm <sup>2</sup>
Fuse type	Electronic
Connected auxiliaries	Maximum 25 auxiliary pushbuttons Maximum 5 auxiliary pushbuttons with light indication
Material	Mechanism cover: ASA + PC
Standards	EN 60669-2-1
Product certifications	Aenor CE
Ambient air temperature for operation	5...30 °C
Ambient air temperature for storage	-20...60 °C
Embedding depth	34 mm
Depth	47 mm
Width	45 mm
Height	45 mm
Product weight	0.078 kg

## Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

## Offer Sustainability

Sustainable offer status	Green Premium product
Product environmental profile	Available
Product end of life instructions	Available

## Contractual warranty

Period	18 months
--------	-----------