



### Main

Commercial Status	Commercialised
Aesthetic name	Unica (standard aesthetic)
Product or component type	1 socket-outlet
Device presentation	Mechanism
Outlet poles configuration	2P + E with shutters
Outlet standard	German
Outlet standard description	Side earth
Rated current	16 A, 250 V AC, 50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Cover plate colour tint	White

### Complementary

Pilot light	LED:
Connections - terminals	Screw terminals
Cable cross section	<= 4 mm <sup>2</sup> (rigid) <= 4 mm <sup>2</sup> (flexible)
Minimum load breaking capacity	100 operations 1.25 I <sub>n</sub> and 1.1 U <sub>n</sub> , cos phi: 0.6
Electrical durability	10000 cycles (cos phi: 0.8)
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	> 2000 V
Material	Mechanism cover: ASA + PC
Quantity per set	Blister: set of 1
Standards	IEC 60884-1 VDE 0620-1 UNE 20315-1-2 BS 1363-1 BS 546:1950 NFC 61-314 NOM-003-SCFI-2000 SI 32
Product certifications	FR.ME63.B02375 AC
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Embedding depth	30 mm
Depth	40 mm
Width	45 mm
Height	45 mm

## Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

## Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0622 - <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Period	18 months
--------	-----------