



Principale

Range name	Sedna
Function	Priza
Delivery form	Produs complet
Configuratie poli priza	2P + E cu obturatoare
Descriere priza standard	Legare la pamant laterala
Curent nominal	16 A la 250 V c.a.
Cover plate color	Alb
Kind of terminals	Borne lift

Suplimentare

Installation	Incastrat
Gama de puteri	3680 W
Terminal capacity	2 cablu(ri) 2,5 mm ²
Wire structure	Flexibil Rigid Impletit solid
Lungime de dezizolare conductor	13 mm
Material of visible parts	ASA + PC
Finisaj suprafata	Glossy
Mod de fixare	Gheare, domeniul de lucru al deschiderii cleștilor 52...69 mm Șuruburi
Înălțime	120 mm
Lățime	84 mm
Adâncime	48 mm
Depth of visual part	23,3 mm
Greutate produs	0,1031 kg

Mediu

Standarde	IEC 60884-1
Grad de protectie IP	IP20

Durabilitatea ofertei

Directiva RoHS UE	Conform Declaratia RoHS UE
Fara mercur	Da
Informatii privind scutirea de la RoHS	Da
Regulamentul RoHS China	Declaratia RoHS China Produs in afara domeniului de aplicare a RoHS China. Declaratia privind substantele in scop informativ.
Raport de mediu	Profilul ambiental al produsului
Profil circularitate	Nu sunt necesare operatii de reciclare speciale

Garantie contractuală

Garantie	18 luni
----------	---------