



Main

Commercial Status	Commercialised
Aesthetic name	Unica Top - Unica Class
Product or component type	Electronic bell
Device presentation	Mechanism
[Ue] rated operational voltage	230 V AC, 50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Cover plate colour tint	Graphite

Complementary

Current consumption	14 mA
Type of setting	5 programmable melodies
Connections - terminals	Screw terminals
Acoustic level	70 dB/1m
Cable cross section	<= 1.5 mm ² (rigid) <= 1.5 mm ² (flexible)
Connected auxiliaries	10 standard pushbuttons connected in parallel 3 indicator lights connected in parallel
Material	Mechanism cover: ASA + PC
Standards	IEC 62080
Product certifications	CE
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Embedding depth	33 mm
Depth	44 mm
Width	45 mm
Height	45 mm
Product weight	0.11 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0805 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Period	18 months
--------	-----------