

# Mosaic™ programme audio/video sockets (continued)



Selection chart for boxes, supports and plates **p. 882-883**

Pack	Cat.Nos	<b>Female RCA sockets</b>
1	0 787 52	<b>Female 1 RCA socket - 1 module</b> Provides the composite video link for any peripheral device such as a DVD drive, camera, video recorder, etc ○ White 
1	0 787 53	<b>Female 2 RCA socket - 1 module</b> Provides the stereo audio link for any peripheral device such as a DVD drive, camera, video recorder ○ White 
1	0 787 54	<b>Female 3 RCA sockets - 1 module</b> Provide the composite video and stereo audio link for any peripheral device such as a DVD drive, camera, video recorder, videoconferencing, etc ○ White ● Alu
1	0 792 54	
<b>Other audio and video sockets</b>		
1	0 787 71	<b>DVI-I socket - 2 modules</b> Used to transmit high-definition digital video streams between a source (computer) and a compatible receiver (plasma, LCD, video projector, etc) ○ White 
1	0 787 69	<b>YUV socket - 1 module</b> Provides the high definition analogue video link for a DVD, PC monitor, plasma screen, etc ○ White 
1	0 787 58	<b>Female BNC 75 socket - 1 module</b> Provides the composite video link for any peripheral device such as a DVD drive, camera, video recorder, etc ○ White 
1	0 787 63	<b>S-Video socket (4-pin mini-DIN) - 1 module</b> Provides the YC video link for any peripheral device such as a DVD drive, camera, video recorder, videoconferencing, etc ○ White 

Pack	Cat.Nos	<b>Audio sockets</b>
10	0 787 55	<b>IXLR 3-pin - 2 modules</b> Provides the stereo link for microphone, amplifier, mixing console, etc. Recommended microphone cable: 1 audio pair 0.22 mm <sup>2</sup> shielded Recommended enclosure cable: 1 audio pair 1.5 mm <sup>2</sup> (can take 2.5 mm <sup>2</sup> ) Max. cable length: 50 m ○ White - Fast screw connection female ● Alu - Fast screw connection female ○ White - Fast screw connection male 
10	0 792 55	
10	0 787 56	
10	0 787 60	<b>4-pole Speakon - 2 modules</b> ○ White - used to connect power enclosures Recommended cable: 1 audio pair 2.5 mm <sup>2</sup> Max. cable length: 50 m (without amplifier) 
<b>Loudspeakers sockets</b>		
10	0 787 51	Terminal 4 mm <sup>2</sup> ○ White - 2 modules 
10	0 787 50	○ White - 1 module ● Alu - 1 module 
10	0 792 50	
10	0 787 75	<b>100 V Line Volume Attenuators - 2 modules</b> Allow to adjust power and volume of a 100 V loudspeaker line ○ White - 100 V - 12 W ○ White - 100 V - 25 W 
10	0 787 76	