



### Main

Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for power outlet
Accessories included with enclosure	1 terminal block 4 holes

### Complementary

Enclosure mounting	Surface
Number of 18 mm modules per row	5
Total number of 18 mm modules	5
Number of horizontal rows	1
Electrical insulation class	Class II Double insulation
Number of openings of interface	1
Provided equipment	1 terminal block 4 holes
Type of front cover	Transparent
Power dissipation in W	12 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	3
Number of terminal blocks	1 with 4 outgoing
Distribution block outgoing	2 x 10 mm <sup>2</sup> 2 x 16 mm <sup>2</sup>
Locking options description	Optional keylock
Enclosure material	Housing : self-extinguishing polymer
Product weight	1.2 kg
Base dimension	103 x 225 mm
Width	138 mm
Height	460 mm
Depth	160 mm
Colour	Door : transparent green Enclosure : light grey ( RAL 7035 )

### Environment

standards	EN 50262 EN 62262 IEC 60439-3 IEC 60529 IEC 60695-2-1 IEC 670
fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
overvoltage category	II

ambient air temperature for operation

-25...40 °C

---

---

### Contractual warranty

Warranty period

18 months

---

---