



Softone ESaver Candle

Softone Candle 8W WW E27 220-240V 1PF/6

Elegant Energy saving lamp with decorative comfort & design, allows easy replacement of most candle shape incandescent lamp.

Product data

General Information	
Cap-Base	E27 [E27]
Nominal Lifetime (Nom)	10000 h
Switching Cycle	30000X
Light Technical	
Color Code	827 [CCT of 2700K]
Luminous Flux (Nom)	370 lm
Luminous Flux (Rated) (Nom)	370 lm
Color Designation	Warm White (WW)
Lumen Maintenance 2000 h (Nom)	83 %
Chromaticity Coordinate X (Nom)	463
Chromaticity Coordinate Y (Nom)	420
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (Rated) (Nom)	46 lm/W
Color Rendering Index (Min)	81
Color Rendering Index (Nom)	82
LLMF At End Of Nominal Lifetime (Nom)	65 %
Operating and Electrical	
Input Frequency	50 or 60 Hz
Power (Rated) (Nom)	8.0 W
Lamp Current (Nom)	60 mA
Wattage Equivalent	35 W

Starting Time (Nom)	1.5 s
Warm Up Time to 60% Light (Min)	10 s
Warm Up Time to 60% Light (Max)	100 s
Power Factor (Nom)	0.6
Voltage (Nom)	220-240 V

Controls and Dimming	
Dimmable	No

Approval and Application	
Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Max)	2.0 mg
Mercury (Hg) Content (Nom)	1.5 mg
Energy Consumption kWh/1000 h	8 kWh


Product Data	
Full product code	871016340527800
Order product name	Softone Candle 8W WW E27 220-240V 1PF/6
EAN/UPC - Product	8710163405278
Order code	929689119302
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929689119302
Net Weight (Piece)	46.000 g

Softone ESaver Candle

Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Dimensional drawing



Product	D (max)	C (max)	F (max)
Softone Candle 8W WW E27 220-240V 1PF/6	41.5 mm	119.0 mm	40 mm

Candle 8W/827 E27 220-240V 50/60Hz

